

KNEE CONNECTORS DETAIL SPECS

CONNECTOR	PICTURE									ADDITIONAL DETAIL INFO.
GUPA-AP4H-ML4H		S	A	10% oz (308 g)	¾ in (2 cm)	4 THREADED (6 mm)	4 THREADED (6 mm)			N/A
GUPA-FCLAMP		A R	A	2¾ oz (70 g)	1 13/16 in (4.7 cm)	Ø 30mm				N/A
GUPA-M4H		A	A S	2¾ oz (70 g)	7/8 in (2.2 cm)		4 UNTHREADED (6 mm)			N/A
GUPA-MLAM		A	A S	2¾ oz (70 g)	¾ in (1.9 cm)	LAM				N/A
GUPAC-FCLAMP		A R	A	1½ oz (46 g)	2 3/16 in (5.5 cm)	Ø 22mm				See Selector Chart "Section 3.2B, p.02"
GUPAC-FCLAMPANG		A R	A	1¾ oz (50 g)	2 1/8 in (5.3 cm)	Ø 22mm 10° Angled				See Selector Chart "Section 3.2C, p.04"
GUPAC-MP1		A R	A S	1¼ oz (36 g)	¾ in (2 cm)		1 THREADED (3/8 SAE)			See Selector Chart "Section 3.2B, p.02"
GUPAC-MCLAMP		A R	A	1¼ oz (50 g)	1 1/4 in (3.3 cm)	Ø 22mm				N/A
GUPAC-MLAM		A	A	1¼ oz (38 g)	¾ in (10 mm)	LAM				N/A
GUPC-FB		N/A	F	3¾ oz (112 g)	1 1/16 in (3.1 cm)	LAM		Lowest of Layup or THREADED		Foam Block
GUPS-FLAM3PRROT		A R	S	5¾ oz (170 g)	7/8 in (2.2 cm)	LAM				N/A
GUPT-F4H		A	T	2½ oz (62 g)	5/8 in (1.6 cm)		4 UNTHREADED (6 mm)			See Selector Chart "Section 3.2C, p.05"

SYMBOL LEGEND™

Material		Alignable	ATTACHMENT METHOD				Dimensions	Maximum Patient Weight	
AA = Aerospace Aluminum	P = Plastic	A = Angular Adj.	1 = 1 Center Hole	Clamp	Male Pyr.	Lamination	Adhesive	Ht. = Ht. Wt. = Wt. Dia. = Dia.	80 lb (36 kg) 220 lb (100 kg)
F = Foam	S = Stainless	R = Rotation	4 = Euro 4-Hole	Ø 30mm = 30mm Pylon	Female Pyr.	Thermoplastic	Bolt Size	Applied Ht. or Thickness	120 lb (54 kg) 243 lb (110 kg)
G = Graph-Lite™	T = Titanium	S = Slide Adjust							165 lb (75 kg) 250 lb (113 kg)
	W = Wood								200 lb (90 kg) high activity



DAW INDUSTRIES



KNEE CONNECTORS DETAIL SPECS

CONNECTOR	PICTURE								ADDITIONAL DETAIL INFO.
GUPT-F4HROT		A R	T	2 7/8 oz (84 g)	5/8 in (1.6 cm)		4 UNTHREADED (6 mm)		See Selector Chart "Section 3.2C, p.05"
GUPT-FCLAMP		A R	T	2 3/8 oz (70 g)	1 13/16 in (4.7 cm)		N/A		See Selector Chart "Section 3.2C, p.06"
GUPT-FF-32M		A	T	3/4 oz (92 g)	1 1/4 in (3.2 cm)				See Selector Chart "Section 3.2C, p.06"
GUPT-FF-45M		A	T	4 1/4 oz (124 g)	1 in (4.5 cm)				See Selector Chart "Section 3.2C, p.06"
GUPT-FF-60M		A	T	3 7/8 oz (110 g)	2 in (6.0 cm)				See Selector Chart
GUPT-FF-75M		A	T	6 1/2 oz (186 g)	3 in (7.5 cm)				See Selector Chart "Section 3.2C, p.06"
GUPT-M4H		A	T	2 oz (186 g)	1/2 in (1.2 cm)		4 UNTHREADED (6 mm)		See Selector Chart "Section 3.2C, p.05"
GUPT-MCLAMP		A R	T	2 3/4 oz (78 g)	1 1/16 in (3.4 cm)				N/A
GUPT-MLAM		A	T	1 3/4 oz (52 g)	7/16 in (1.1 cm)			Lowest of Layup or	N/A
G4H-SCREWNUTSET		N/A	S	3/4 oz (22 g)	N/A	6 mm flathead screw (14 mm) (Set of 4)	6 mm flathead nuts (Set of 4)		Set of 4 screws & countersunk nuts.

SYMBOL LEGEND™

Material		Attachment Method	Dimensions	Maximum Patient Weight
A = Aluminum Alloy AA = Aerospace Aluminum F = Foam G = Graph-Lite™ P = Plastic S = Stainless T = Titanium W = Wood	A = Angular Adj. R = Rotation S = Slide Adjust	1 = 1 Center Hole 4 = Euro 4-Hole C = Clamp M = Male Pyr. F = Female Pyr. L = Lamination A = Adhesive T = Thermoplastic	Ht. = Ht. Wt. = Wt. Dia. = Dia. Bolt Size = Bolt Size Applied Ht. or Thickness = Applied Ht. or Thickness Circ. = Circ.	80 lb (36 kg) 120 lb (54 kg) 165 lb (75 kg) 200 lb (90 kg) 220 lb (100 kg) 243 lb (110 kg) 250 lb (113 kg) High activity



DAW INDUSTRIES



KNEE CONNECTORS DETAIL SPECS

CONNECTOR	PICTURE								ADDITIONAL DETAIL INFO.
RSC-SA				8 oz (228 g)	1 3/8 in (3.5 cm)				N/A
TGB-Ø				4 oz (114 g)	2 1/4 in (5.7 cm)				Foam Block
TGB-ØT				6 oz (174 g)	12 1/4 in (31 cm)				See Selector Chart "Section 3.2B, p.01"
TGC-ØA				4 3/8 oz (126 g)	2 1/2 in (6.3 cm)		 		15° Preset Angle for Adult Hip Application
TKC-ØA				6 3/8 oz (182 g)	2 3/4 in (7 cm)		 		15° Preset Angle for Adult Hip Application
TKC-C4				1 3/8 oz (38 g)	3/16 in (5 mm)				To be used only with TK-4ØC or TK-1C1.
TKC-CA				2 3/8 oz (68 g)	1 in (4.8 cm)				15° Preset Angle for Child Hip Application
TKC-S				4 1/8 oz (120 g)	3/8 in (10 mm)				To be used with Adult 4-Threaded Holes and Center Bolt Knees
TKC-SA				5 3/8 oz (168 g)	3/4 in (1.9 cm)				See Selector Chart "Section 3.2B, p.01"
TKR-Ø1				6 3/8 oz (188 g)	3/4 in (1.9 cm)		 		N/A
TSC-A				4 3/8 oz (124 g)	1/2 in (1.3 cm)		 		See Selector Chart "Section 3.2B, p.01"
TSC-BX		N/A		2 1/2 oz (72 g)	3/8 in (10 mm)				N/A

SYMBOL LEGEND™

Material		Alignable	ATTACHMENT METHOD				Dimensions	Maximum Patient Weight	



DAW
INDUSTRIES



KNEE CONNECTORS DETAIL SPECS

CONNECTOR	PICTURE								ADDITIONAL DETAIL INFO.
TSC-KDA-L			A	3 3/8 oz (106 g)	5/16 in (8 mm)				To be used with Adult 4-Threaded Holes and Center Bolt Knees
TSC-KDL			S	8 3/4 oz (248 g)	1/4 in (6 mm)				To be used with Adult 4-Threaded Holes and Center Bolt Knees
TSC-KDC-AL			AA	1 1/8 oz	1/4 in (6 mm)			60 lbs. (27 kg)	To be used only with TK-40C or TK-1C1
TSC-KDC-L			S	3 3/8 oz (106 g)	3/16 in (5 mm)				To be used only with TK-40C or TK-1C1
TSC-LPØ		N/A	RUBBER	1 1/4 oz (36 g)	3/4 in (19 mm)	SNAP ON	N/A	N/A	Fabricating Plug for "TSC" L-Brackets
TSC-LP1		N/A	RUBBER	1 3/8 oz (40 g)	1 in (2.5 cm)	SNAP ON	N/A	N/A	Fabricating Plug for Wood Blocks & Wire Baskets
TSC-PSD			AA	1 1/2 oz (44 g)	1/4 in (6 mm)				N/A
TSC-PSDS			S	3 oz (88 g)	3/16 in (5 mm)				To be used with Adult 4-Threaded Holes and Center Bolt Knees
TSC-T		N/A	AA	1 7/8 oz (54 g)	5/16 in (8 mm)				See Selector Chart "Section 3.2C, p.05"
TSC-WC			AA	2 1/4 oz (66 g)	3/4 in (19 mm)			Child Level I Adult	N/A
TTB-1			AA	5 3/8 oz (162 g)	2 3/8 in (6 cm)				See Selector Chart "Section 3.2B, p.01"

* Type "T" Knee = DAW Adult knees which stock number starts with a "T"

SYMBOL LEGEND™

Material		Alignable	ATTACHMENT METHOD				Dimensions	Maximum Patient Weight													
A = Aluminum Alloy	P = Plastic																				
AA = Aerospace Aluminum	S = Stainless																				
F = Foam	T = Titanium																				
G = Graph-Lite™	W = Wood																				



DAW INDUSTRIES



KNEE CONNECTORS DETAIL SPECS

CONNECTOR #	PICTURE								ADDITIONAL DETAIL INFO.
TWB-Ø4			W	17¼ oz (560 g) Untrimmed	2½ in (6.3 cm) Untrimmed		 		N/A
TWB-C			W	2¾ oz (68 g) Untrimmed	1¾ in (3.1 cm) Untrimmed				AK – Child & Adolescent See Selector Chart "Section 3.2B, p.02"
TWP-A2A	 2¼ in (68 mm)		AA	2½ oz (64 g)	2¼ in (68 mm)				N/A
TWP-C2	 7/16 in (8.8 mm)		NYLON	¾ oz (10 g)	5/16 in (8.8 mm)				N/A

* Type "T" Knee = DAW Adult knees which stock number starts with a "T"

SYMBOL LEGEND™

Material		Alignable	ATTACHMENT METHOD			Dimensions	Maximum Patient Weight
A = Aluminum Alloy AA = Aerospace Aluminum F = Foam G = Graph-Lite™	P = Plastic S = Stainless T = Titanium W = Wood	 	 	 	 	 	



DAW INDUSTRIES

