





























































































































KNEE CONNECTORS DETAIL SPECS

CONNECTOR	PICTURE								ADDITIONAL DETAIL INFO.
GUPA-AP4H-ML4H				10% oz (308 g)	¾ in (2 cm)	 THREADED (6 mm)	 THREADED (6 mm)		N/A
GUPA-FCLAMP				2⅜ oz (70 g)	1⅜ in (4.7 cm)	 Ø 30mm			N/A
GUPA-M4H			 	2⅜ oz (70 g)	⅞ in (2.2 cm)		 UNTHREADED (6 mm)		N/A
GUPA-MLAM			 	2⅜ oz (70 g)	¾ in (1.9 cm)	 LAM.			N/A
GUPAC-FCLAMP		 		1⅝ oz (46 g)	2 ⅜ in (5.5 cm)	 Ø 22mm			See Selector Chart "Section 3.2B, p.02"
GUPAC-FCLAMPANG		 		1¾ oz (50 g)	2⅝ in (5.3 cm)	 Ø 22mm 10° Angled			See Selector Chart "Section 3.2C, p.04"
GUPAC-MP1		 	 	1¼ oz (36 g)	¾ in (2 cm)		 THREADED (3/8 SAE)		See Selector Chart "Section 3.2B, p.02"
GUPAC-MCLAMP		 		1¼ oz (50 g)	1¼ in (3.3 cm)		 Ø 22mm		N/A
GUPAC-MLAM				1¼ oz (38 g)	⅝ in (10 mm)	 LAM.			N/A
GUPC-FB		 N/A		3⅜ oz (112 g)	1⅜ in (3.1 cm)	 LAM.	 THREADED	 Lowest of Layup or	Foam Block
GUPS-FLAM3PRROT		 		5% oz (170 g)	⅞ in (2.2 cm)	 LAM.			N/A
GUPT-F4H				2⅝ oz (62 g)	⅝ in (1.6 cm)		 UNTHREADED (6 mm)		See Selector Chart "Section 3.2C, p.05"

SYMBOL LEGEND™

 = Material		 = Alignable		ATTACHMENT METHOD		 = Dimensions		 = Maximum Patient Weight	
 = Aluminum Alloy	 = Plastic	 = Angular Adj.	 = 1 Center Hole	 = Clamp	 = Male Pyr.	 = Lamination	 = Adhesive	 = 1 = Ht.	 = Wt.
 = Aerospace Aluminum	 = Stainless	 = Rotation	 = Euro 4-Hole	 = 30mm Pylon	 = Female Pyr.	 = Thermoplastic	 = Bolt Size	 = Applied Ht. or Thickness	 = Circ.
 = Foam	 = Titanium	 = Slide Adjust							
 = Graph-Lite™	 = Wood								
								 = 80 lb (36 kg)	 = 220 lb (100 kg)
								 = 120 lb (54 kg)	 = 243 lb (110 kg)
								 = 165 lb (75 kg)	 = 250 lb (113 kg)
								 = 200 lb (90 kg)	 = high activity


































































DAW
INDUSTRIES

© Copyright 2015, DAW Industries, San Diego, CA. All Rights Reserved.































Orders (800) 252-2828 • Technical Hotline (877) 242-2423 • www.daw-usa.com



KNEE CONNECTORS DETAIL SPECS

CONNECTOR	PICTURE								ADDITIONAL DETAIL INFO.
GUPT-F4HROT				2 $\frac{7}{8}$ oz (84 g)	$\frac{5}{8}$ in (1.6 cm)		 UNTHREADED (6 mm)		See Selector Chart "Section 3.2C, p.05"
GUPT-FCLAMP				2 $\frac{3}{8}$ oz (70 g)	1 $\frac{13}{16}$ in (4.7 cm)	 Ø 30mm	N/A		See Selector Chart "Section 3.2C, p.06"
GUPT-FF-32M				3 $\frac{1}{4}$ oz (92 g)	1 $\frac{1}{4}$ in (3.2 cm)				See Selector Chart "Section 3.2C, p.06"
GUPT-FF-45M				4 $\frac{1}{4}$ oz (124 g)	1 $\frac{1}{4}$ in (4.5 cm)				See Selector Chart "Section 3.2C, p.06"
GUPT-FF-60M				3 $\frac{7}{8}$ oz (110 g)	2 $\frac{1}{8}$ in (6.0 cm)				See Selector Chart
GUPT-FF-75M				6 $\frac{1}{2}$ oz (186 g)	3 in (7.5 cm)				See Selector Chart "Section 3.2C, p.06"
GUPT-M4H				2 oz (186 g)	$\frac{1}{2}$ in (1.2 cm)		 UNTHREADED (6 mm)		See Selector Chart "Section 3.2C, p.05"
GUPT-MCLAMP				2 $\frac{3}{4}$ oz (78 g)	1 $\frac{1}{16}$ in (3.4 cm)		 Ø 30mm		N/A
GUPT-MLAM				1 $\frac{1}{4}$ oz (52 g)	$\frac{7}{16}$ in (1.1 cm)				N/A
G4H- SCREWNUTSET		N/A		$\frac{3}{4}$ oz (22 g)	N/A	6 mm flathead screw (14 mm) (Set of 4)	6 mm flathead nuts (Set of 4)		Set of 4 screws & countersunk nuts.

SYMBOL LEGEND™

 = Material	 = Alignable	ATTACHMENT METHOD				 = Dimensions	 = Maximum Patient Weight
 = Aluminum Alloy	 = Angular Adj.	 = 1 Center Hole	 = Clamp	 = Male Pyr.	 = Lamination	 = Adhesive	 = 80 lb (36 kg)
 = Aerospace Aluminum	 = Rotation	 = Euro 4-Hole	 = 30mm Pylon	 = Female Pyr.	 = Thermoplastic	 = Bolt Size	 = 120 lb (54 kg)
 = Foam	 = Slide Adjust						 = 165 lb (75 kg)
 = Graph-Lite™							 = 200 lb (90 kg)
 = Wood							 = 220 lb (100 kg)
							 = 243 lb (110 kg)
							 = 250 lb (113 kg)
							 = High activity



DAW
INDUSTRIES

© Copyright 2015, DAW Industries, San Diego, CA. All Rights Reserved.

Orders (800) 252-2828 • Technical Hotline (877) 242-2423 • www.daw-usa.com



KNEE CONNECTORS DETAIL SPECS

CONNECTOR	PICTURE								ADDITIONAL DETAIL INFO.
RSC-SA				8 oz (228 g)	1 3/8 in (3.5 cm)	 UNTHREADED (6 mm)	 THREADED (6 mm)		N/A
TGB-Ø				4 oz (114 g)	2 1/4 in (5.7 cm)	 UNTHREADED (6 mm)	 Ø 30mm		Foam Block
TGB-ØT				6 oz (174 g)	12 1/4 in (31 cm)	 UNTHREADED (6 mm)	 Ø 30mm		See Selector Chart "Section 3.2B, p.01"
TGC-ØA				4 3/8 oz (126 g)	2 1/2 in (6.3 cm)	 Ø 30mm	 THREADED UNTHREADED		15° Preset Angle for Adult Hip Application
TKC-ØA				6 3/8 oz (182 g)	2 3/4 in (7 cm)	 Ø 30mm	 THREADED UNTHREADED		15° Preset Angle for Adult Hip Application
TKC-C4				1 3/8 oz (38 g)	3/16 in (5 mm)	 UNTHREADED (6 mm)	 THREADED (3/8 SAE)		To be used only with TK-40C or TK-1C1.
TKC-CA				2 3/8 oz (68 g)	1 in (4.8 cm)	 Ø 30mm	 THREADED (3/8 SAE)		15° Preset Angle for Child Hip Application
TKC-S				4 3/8 oz (120 g)	3/8 in (10 mm)	 UNTHREADED (6 mm)	 THREADED (7/16 SAE)		To be used with Adult 4-Threaded Holes and Center Bolt Knees
TKC-SA				5 3/8 oz (168 g)	3/4 in (1.9 cm)	 UNTHREADED (6 mm)	 THREADED (7/16 SAE)		See Selector Chart "Section 3.2B, p.01"
TKR-Ø1				6 3/8 oz (188 g)	3/4 in (1.9 cm)	 UNTHREADED (6 mm)	 THREADED (7/16 SAE) THREADED (6 mm)		N/A
TSC-A				4 3/8 oz (124 g)	1/2 in (1.3 cm)		 THREADED (7/16 SAE) THREADED (6 mm)		See Selector Chart "Section 3.2B, p.01"
TSC-BX		N/A		2 1/2 oz (72 g)	3/8 in (10 mm)		 THREADED (6 mm)		N/A

SYMBOL LEGEND™

		ATTACHMENT METHOD			































































DAW
INDUSTRIES

© Copyright 2015, DAW Industries, San Diego, CA. All Rights Reserved.

Orders (800) 252-2828 • Technical Hotline (877) 242-2423 • www.daw-usa.com


































KNEE CONNECTORS DETAIL SPECS

CONNECTOR	PICTURE								ADDITIONAL DETAIL INFO.
TSC-KDA-L				3 $\frac{3}{8}$ oz (106 g)	$\frac{5}{16}$ in (8 mm)		 THREADED (7/16 SAE)		To be used with Adult 4-Threaded Holes and Center Bolt Knees
TSC-KDL				8 $\frac{3}{4}$ oz (248 g)	$\frac{1}{4}$ in (6 mm)		 THREADED (7/16 SAE)		To be used with Adult 4-Threaded Holes and Center Bolt Knees
TSC-KDC-AL				1 $\frac{1}{8}$ oz	$\frac{1}{4}$ in (6 mm)		 THREADED (3/8 SAE)	60 lbs. (27 kg)	To be used only with TK-40C or TK-1C1
TSC-KDC-L				3 $\frac{3}{8}$ oz (106 g)	$\frac{3}{16}$ in (5 mm)		 THREADED (3/8 SAE)		To be used only with TK-40C or TK-1C1
TSC-LPØ		N/A	RUBBER	1 $\frac{1}{4}$ oz (36 g)	$\frac{3}{4}$ in (19 mm)	SNAP ON	N/A	N/A	Fabricating Plug for "TSC" L-Brackets
TSC-LP1		N/A	RUBBER	1 $\frac{1}{8}$ oz (40 g)	1 in (2.5 cm)	SNAP ON	N/A	N/A	Fabricating Plug for Wood Blocks & Wire Baskets
TSC-PSD				1 $\frac{1}{2}$ oz (44 g)	$\frac{1}{4}$ in (6 mm)	 UNTHREADED (6 mm)	 THREADED (7/16 SAE)		N/A
TSC-PSDS				3 oz (88 g)	$\frac{3}{16}$ in (5 mm)	 UNTHREADED (6 mm)	 THREADED (7/16 SAE)		To be used with Adult 4-Threaded Holes and Center Bolt Knees
TSC-T		N/A		1 $\frac{1}{8}$ oz (54 g)	$\frac{5}{16}$ in (8 mm)		 THREADED (6mm)		See Selector Chart "Section 3.2C, p.05"
TSC-WC				2 $\frac{1}{4}$ oz (66 g)	$\frac{3}{4}$ in (19 mm)		 THREADED (3/8 SAE)	Child Level I Adult	N/A
TTB-1				5 $\frac{5}{8}$ oz (162 g)	2 $\frac{3}{8}$ in (6 cm)		 THREADED (7/16 SAE)		See Selector Chart "Section 3.2B, p.01"

* Type "T" Knee = DAW Adult knees which stock number starts with a "T"

SYMBOL LEGEND™

Material		Attachment Method		Dimensions	
					
					
					
					
					
					
					
					




































DAW
INDUSTRIES

© Copyright 2015, DAW Industries, San Diego, CA. All Rights Reserved.

Orders (800) 252-2828 • Technical Hotline (877) 242-2423 • www.daw-usa.com









KNEE CONNECTORS DETAIL SPECS

CONNECTOR #	PICTURE								ADDITIONAL DETAIL INFO.
TWB-Ø4				17¼ oz (560 g) Untrimmed	2½ in (6.3 cm) Untrimmed		 THREADED (7/16 SAE)  THREADED (6mm)		N/A
TWB-C				2¾ oz (68 g) Untrimmed	1⅞ in (3.1 cm) Untrimmed		 THREADED (3/8 SAE)	 Level I Adult	AK – Child & Adolescent See Selector Chart “Section 3.2B, p.02”
TWP-A2A	 2⅞ in (68 mm)	 		2⅞ oz (64 g)	2⅞ in (68 mm)	 UNTHREADED (7/16 SAE)	 UNTHREADED (7/16 SAE)		N/A
TWP-C2	 7/16 in (8.8 mm)	 	NYLON	¾ oz (10 g)	5/16 in (8.8 mm)	 UNTHREADED (3/8 SAE)	 UNTHREADED (3/8 SAE)	 Level I Adult	N/A

* Type “T” Knee = DAW Adult knees which stock number starts with a “T”

SYMBOL LEGEND™

Material		Alignable		ATTACHMENT METHOD				Dimensions		Maximum Patient Weight	
	= Material		= Alignable		= Top		= Bottom		= Dimensions		= Maximum Patient Weight
A = Aluminum Alloy	P = Plastic	⊕ = Angular Adj.	⊙ = 1 Center Hole	⊕ = Clamp	⊕ = Male Pyr.	⊕ = Lamination	⊕ = Adhesive	1 = Ht.	⊕ = Wt.	⊕ = Dia.	⊕ = 80 lb (36 kg)
AA = Aerospace Aluminum	S = Stainless	⊙ = Rotation	⊕ = Euro 4-Hole	⊕ = 30mm = 30mm Pylon	⊕ = Female Pyr.	⊕ = Thermoplastic	⊕ = Bolt Size	⊕ = Applied Ht. or Thickness	⊕ = Circ.	⊕ = 120 lb (54 kg)	⊕ = 220 lb (100 kg)
F = Foam	T = Titanium	⊕ = Slide Adjust								⊕ = 165 lb (75 kg)	⊕ = 243 lb (110 kg)
G = Graph-Lite™	W = Wood									⊕ = 200 lb (90 kg)	⊕ = 250 lb (113 kg)



DAW
INDUSTRIES

© Copyright 2015, DAW Industries, San Diego, CA. All Rights Reserved.

Orders (800) 252-2828 • Technical Hotline (877) 242-2423 • www.daw-usa.com

