





















HEIGHT ADJUSTABLE PYLONS

Standard Pylon

	Stock Number							
	TTC-15	A	 Ø 22mm	 Ø 22mm	4 1/2 oz (128 g)	Child & Adolescent Level 1 Adult	15 in (38 cm)	R

Pylons with Female Pyramid

	Stock Number							
	GUPAC-FPYLON-6	A	 Ø 22mm		2 1/4 oz (64 g)	Child & Adolescent Level 1 Adult	13 in (33 cm)	A

S Y M B O L E G E N D™

Material		Alignable	ATTACHMENT METHOD				Dimensions		Maximum Patient Weight			
			Top	Bottom								
A = Aluminum Alloy	P = Plastic	⊕ = Angular Adj.	⊙ = 1 Center Hole	⊔ = Clamp	⊖ = Male Pyl.	⊕ = Lamination	⊔ = Adhesive	⊔ = Ht.	⊖ = Wt.	⊙ = Dia.	⊕ = 80 lb (36 kg)	⊖ = 220 lb (100 kg)
Al = Aerospace Aluminum	S = Stainless	⊖ = Rotation	⊔ = Euro 4-Hole	⊔ = 30mm = 30mm Pylon	⊖ = Female Pyl.	⊔ = Thermoplastic	⊔ = Bolt Size	⊔ = Applied Ht. or Thickness	⊖ = Circ.	⊕ = 120 lb (54 kg)	⊖ = 243 lb (110 kg)	
F = Foam	T = Titanium	⊕ = Slide Adjust									⊕ = 165 lb (75 kg)	⊖ = 250 lb (113 kg)
G = Graph-Lite™	W = Wood										⊕ = 200 lb (90 kg)	⊖ = high activity



DAW INDUSTRIES

